

# SAFETY DATA SHEET

## SECTION 1 - Product & Company Identification

Product Name: HS LTC White One Coat Marine Epoxy - Part A Product Code: RCT 03 1064 EP

Rapid Cure Technologies  
7030 Fly Road  
East Syracuse, NY 13057  
1-888-847-3610

Emergency Phone (Day)  
M-F 8a-4p EST: 1-888-847-3610

Emergency Phone (Night)  
All other Hours: 1-800-424-9300 Chemtrec

Product Use: Epoxy Coating  
Not recommended for: Residential Use

## SECTION 2 - Hazards Identification

### GHS Ratings:

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation
Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days
Skin sensitizer	1	Skin sensitizer

### GHS Hazards

H225	Highly flammable liquid and vapour
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation

### GHS Precautions

P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
P233	Keep container tightly closed
P240	Ground/bond container and receiving equipment
P241	Use explosion-proof electrical/ventilating/lighting equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P264	Wash skin thoroughly after handling
P272	Contaminated work clothing should not be allowed out of the workplace
P280	Wear protective gloves/protective clothing/eye protection/face protection
P321	Specific treatment (see ... on this label)
P362	Take off contaminated clothing and wash before reuse
P363	Wash contaminated clothing before reuse
P302+P352	IF ON SKIN: Wash with soap and water
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P332+P313	If skin irritation occurs: Get medical advice/attention
P333+P313	If skin irritation or a rash occurs: Get medical advice/attention
P337+P313	If eye irritation persists, get medical advice/attention

P370+P378

In case of fire: Use water spray, carbon dioxide (CO<sub>2</sub>), dry powder or dry chemical foam for extinction

P403+P235

Store in a well ventilated place. Keep cool

P501

Dispose of contents/container in accordance with all local, jurisdictional, national and international regulations.

**Signal Word: Danger**



### SECTION 3 - Composition / Information on Ingredients

Chemical Name	CAS number	Weight Concentration %
Bisphenol A epoxy resin	25068-38-6	20.00% - 30.00%
Bisphenol A/Bisphenol A diglycidyl ether polymer	25036-25-3	20.00% - 30.00%
Methyl ethyl ketone	78-93-3	10.00% - 20.00%
Unsaturated long chain ether alcohol	232268-65-4	10.00% - 20.00%
Titanium dioxide	13463-67-7	5.00% - 10.00%
Calcium carbonate	1317-65-3	5.00% - 10.00%
Amorphous silica	67762-90-7	1.00% - 5.00%

### SECTION 4 - First Aid Measures

**INHALATION:** Move subject to fresh air and keep warm. If subject is not breathing, administer artificial respiration. If breathing is difficult, have qualified personnel administer oxygen and get medical attention.

**EYE CONTACT:** Flush the eye and under the lids with warm water for 15 minutes. Remove any contact lenses during the flushing. Get immediate medical attention if symptoms persist.

**SKIN CONTACT:** Remove and isolate contaminated clothing and shoes. Remove excess material from skin with clean cloth. Flush skin with running lukewarm water. Wash affected area using mild soap.

**INGESTION:** If appreciatble quantities are swallowed, seek immediate medical attention.

### SECTION 5 - Firefighting Measures

Flash Point: -1 C (30 F)

LEL: 2.0%

UEL: 12.0%

**EXTINGUISHING MEDIA:** Water spray, dry powder, carbon dioxide (CO<sub>2</sub>) or dry chemical foam. Do not use a solid water stream as it may scatter and spread fire.

**ADVICE FOR FIREFIGHTERS:** Vapors may form explosive mixtures with air. Most vapors are heavier than air. They will spread along the ground and collect in confined or low areas. Vapors may travel to source of ignition and flash back. As in any fire wear a self-contained breathing apparatus and full protective gear. Do not enter a fire area without proper protective equipment.

### SECTION 6 - Accidental Release Measures

**SPILL PROCEDURES:** Remove all sources of ignition and ventilate area. Avoid skin and eye contact. Use respiratory protection. Absorb with inert materials such as dry clay or sand and place in a closed container for disposal as solid waste in accordance with applicable regulations.

**ENVIRONMENTAL PRECAUTIONS:** Do not empty into drains. Do not discharge into drains/surface water/groundwater.

**SECTION 7 - Handling and Storage**

**HANDLING:** Keep away from open flames, sources of ignition and hot surfaces. Avoid conditions that could lead to static discharge. Ground all metal parts/containers. Avoid any unnecessary contact. Do not breathe vapors, spray or mist. Use protective clothing specified in Section 8.

**STORAGE:** Store away from heat and sunlight to prevent polymerization. Keep away from open flames, ignition sources and hot surfaces. Polymerization initiators include peroxides, strong oxidizers, strong acids & strong bases.

**SECTION 8 - Exposure Controls / Personal Protection**

<b>Chemical Name / CAS No.</b>	<b>OSHA Exposure Limits</b>	<b>ACGIH Exposure Limits</b>	<b>Other Exposure Limits</b>
Bisphenol A epoxy resin 25068-38-6	Not Established	Not Established	Not Established
Bisphenol A/Bisphenol A diglycidyl ether polymer 25036-25-3	Not Established	Not Established	Not Established
Methyl ethyl ketone 78-93-3	PEL 200ppm, 590mg/m3	TLV (8-hour) 200ppm, 590mg/m3 STEL 300ppm, 885mg/m3	Not Established
Unsaturated long chain ether alcohol 232268-65-4	Not Established	Not Established	Not Established
Titanium dioxide 13463-67-7	PEL: 15mg/m3 8 hr. TWA Total Dust	10mg/m3 TWA	Not Established
Calcium carbonate 1317-65-3	Not Established	Not Established	Not Established
Amorphous silica 67762-90-7	Not Established	Not Established	Not Established

**ENGINEERING CONTROLS:** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use explosion proof ventilation equipment and non-sparking tools.

**HAND PROTECTION:** Use nitrile, butyl, neoprene or other gloves that are resistant to chemicals in Section 3. Replace immediately if punctured, torn or when change of appearance (color, elasticity, shape) occurs.

**EYE PROTECTION:** Use splash-proof safety goggles, safety glasses or face shields that are ANSI approved to prevent eye contact. Eye wash availability is also recommended.

**SKIN PROTECTION:** Protective or disposable outer clothing is recommended. Protective clothing must be thoroughly cleaned after each use.

**RESPIRATORY PROTECTION:** Use local exhaust to control vapors and mists. Use of a NIOSH approved respirator for organic vapors is recommended if TLV is exceeded.

CONTAMINATED GEAR: Lightly contaminated clothing may be laundered but separately from daily use clothing .  
 Heavily contaminated clothing, including shoes and other PPE should be disposed of.

SECTION 9 - Physical and Chemical Properties

<p><b>Physical State:</b> Liquid</p> <p><b>Odor:</b> Ketone</p> <p><b>pH:</b> N/A</p> <p><b>Boiling Point/Range:</b> N/A</p> <p><b>Evaporation Rate:</b> N/A</p> <p><b>LEL:</b> N/A</p> <p><b>Vapor Pressure:</b> N/A</p> <p><b>Lbs/Gal:</b> 10.29</p> <p><b>Partition Coefficient (n- octanol/water):</b> N/A</p> <p><b>Decomposition Temperature:</b> N/A</p> <p><b>VOC:</b> 1.43 lbs/gal</p>	<p><b>Color:</b> White</p> <p><b>Odor Threshold:</b> N/A</p> <p><b>Freezing/Melting Point:</b> N/A</p> <p><b>Flash Point:</b> 31°F</p> <p><b>Flammability:</b> N/A</p> <p><b>UEL:</b> N/A</p> <p><b>Vapor Density:</b> N/A</p> <p><b>Solubility:</b> N/A</p> <p><b>Autoignition Temperature:</b> N/A</p> <p><b>Viscosity KU:</b> 120-125</p>
---	--

SECTION 10 - Stability and Reactivity

STABILITY: Product is stable under recommended storage conditions . Refer to Section 7.

STABLE

CONDITIONS TO AVOID: Excessive heat, ignition sources, exposure to direct sunlight and contamination with foreign materials.

None

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal oxidation or pyrolysis (as in fire) may yield carbon dioxide, carbon monoxide and volatile organic compounds, which can be flammable, irritating, corrosive or toxic.

None

Hazardous polymerization will not occur.

SECTION 11 - Toxicological Information

**Mixture Toxicity**

Inhalation Toxicity LC50: 70mg/L

**Component Toxicity**

78-93-3	Methyl ethyl ketone
	Oral LD50: 2,483 mg/kg (Rat)
13463-67-7	Titanium dioxide
	Inhalation LC50: 7 mg/L (Rat)

Eye Contact

None

**Effects of Overexposure**

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
None			None

SECTION 12 - Ecological Information

**General Notes** - Avoid release to the environment.

**Component Ecotoxicity**

Titanium dioxide	96 Hr LC50: Pimephales promelas: > 1000 mg/L
	72 Hr EC50: Pseudokirchneriella subcapitata: > 100 mg/L
	48 Hr EC50: Daphnia magna: > 1000 mg/L

SECTION 13 - Disposal Considerations

**Waste from Residues/Unused Products** - Dispose of in accordance with local regulations.

**Contaminated Packaging** - Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14 - Transportation Information

**Disclaimer** - Any given paint product can be shipped in different size containers, ranging from a pint can to bulk tanks. The shipping regulations in the United States vary depending on container size. The Basic Description given below are for shipments in fully regulated, non-bulk containers, where the UN ID Number, Proper Shipping Name, (technical names, if any), Packing Groups & Hazard Class (subsidiary risks, if any) are given. This section does not cover packaging exceptions, such as smaller quantities that can be shipping in combination packaging i.e. Limited Quantities or Consumer Commodities with or without basic descriptions or shipping papers. Not covered are exceptions given for products that do not sustain combustion and are exempted from regulation under certain modes of transportation. Products containing Reportable Quantities (RQ's) of hazardous substances when shipped in bulk, but not reportable when shipped in non-bulk packaging are not covered either. All subsequent shipping of this product must be done by properly trained and certified employees under the specific competent authority's regulations.

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	PAINT	UN1263	II	3
IATA	PAINT	UN1263	II	3
IMDG	PAINT	UN1263	II	3

SECTION 15 - Regulatory Information

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material. The following items are reportable under SARA 313:

None

This product contains the following chemicals which are listed by the state of California as carcinogenic or a reproductive toxin:

None

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>
USA	TSCA	No
Canada	DSL	No

**EU Risk Phrases**

**Safety Phrase**

None

SECTION 16 - Other Information

DISCLAIMER: To the best of our knowledge, the product information contained herein is based upon data believed to be reliable, however makes no warranty and disclaims any liability whatsoever for its accuracy or completeness. Since the actual use of this product is beyond our control, no guarantee expressed or implied, is made by Rapid Cure Technologies, Inc. as to the effects of such uses nor does Rapid Cure Technologies, Inc. assume liability arising out of the use of this product by others. It remains the responsibility of the user to ensure that the product herein is in accordance with all applicable laws and regulations.

Date revised: 2020-12-10

Reviewer Revision 1

Date Prepared: 12/10/2020